



HYDROGEN

Valves • Actuators • Automation Technology





SOLUTIONS FOR VARIOUS APPLICATIONS.

Water treatment / demineralization Cooling systems Gas supply (natural gas / biogas) Electrolysis (AEL, PEM, AEM, HTEL) Steam reforming Methane pyrolysis Separation Filtration Gas drying Oxygen handling Physical storage Chemical storage Power generation Mobility Industrial applications Transportation in pipelines



Guaranteed certified:

To guarantee the conformity of our products, we consistently adhere to the current directives and regulations, ensuring that all products used comply with the strictest standards and regulations for safe facility operation.

- Pressure Equipment Directive 2014/68/EU
- Gas Appliance Regulation EU/2016/426
 - DVGW Gas
 - EN 161
 - Explosion Protection ATEX 2014/34/EU
 - SIL (IEC 61508 Level 3)
 - Fugitive Emissions ISO 15848-1 | TA Luft

FORWARD-THINKING. INNOVATIVE.

Industrial shut-off and control valves. High-performance solutions for hydrogen production.

Hydrogen is increasingly seen as a key technology for energy transition and the decarbonization of varoius sectors. Its versatility as both an energy carrier and a raw material makes it an essential element in future energy and industrial policies.

Butterfly valves are used in a wide range of applications, from hydrogen production and transport to storage and utilization in fuel cells. Particularly in the emerging field of hydrogen mobility and industrial processes, where hydrogen serves as an energy carrier or raw material, reliable and safe butterfly valves are essential.

Hydrogen technology imposes specific requirements on butterfly valves. H2 has unique physical and chemical properties that require special consideration.

EBRO: YOUR RELIABLE PARTNER

For decades, EBRO valves have been trusted worldwide for their reliability and durability, particularly in demanding applications. The processes involved in hydrogen production are no exception. EBRO has the benefit of knowledge in chemical and hazardous media and can draw on extensive experience and expertise in this area. Our customized products ensure smooth and extremely economical operation.

THE EXCELLENT SAFETY AND QUALITY OF OUR PRODUCTS ENSURE THAT YOUR SYSTEM IS SAFE AND RELIABLE:

- **Resource-efficient operational management:** we focus on efficiency, thanks to optimal coordination of valves with suitable actuator and automation technology
- Significant reduction in operating costs: due to improved system performance and reliability
- Sustainable and economical operational management: through minimized energy consumption and optimized processes
- Certified safety: our products are approved in accordance with ATEX, SIL, EN 161 and DVGW-Gas
- Future-orientated solutions: continuous research and development allows EBRO to stay ahead in our field and bring innovation





HIGH PERFORMANCE VALVES

Reliable under extreme conditions

The double eccentric design, high-quality materials and precision machining ensure safety even under extreme operating conditions.

The HP valve is commonly used in areas such as separation, oxygen handling, distribution infrastructure, and storage.

For use in potentially explosive atmospheres, an ATEX type certification is available up to category 1 GD (Zone 0 and 20).

Marking for explosive gas group IIC prevailing in H2 atmospheres is possible.



More information on High-Performance valves.



HP114-C Lug-type DN 80 – DN 400



HP112 Double-flanged DN 80 – DN 600



HP111 Wafer-type DN 700 – DN 1200



HP114 Lug-type DN 700 – DN 1200



Durable and safe

PTFE-lined butterfly and control valves are specially designed for use in chemically aggressive alkalis and acids. The minimum 3 mm thick lining made of pure PTFE guarantees optimum protection and ensures non-contact with metallic components with PTFEcoated discs.

In conjunction with live loaded double shaft sealing, this valve series offers maximum operational safety.

PTFE valves are typically used in processes involving demineralized water.



More information on PTFE valves.



T211-A Wafer-type DN 50 – DN 300



T212-A Double-flanged DN 350 – DN 1000



T214-A Lug-type DN 50 – DN 300

RESILIENT SEATED VALVES

Versatile and reliable

The resilient seated butterfly valves with triple shaft bearing and replaceable liner have a wide range of applications, for example in cooling and water circuits as well as gas supply systems.

Depending on the configuration and material combination, these valves can also be used in applications with up to 100% hydrogen content.

DVGW gas and EN 161 certified versions are available. Special disc coatings like ECTFE or Rilsan® are also offered depending on the application.

For use in potentially explosive atmospheres, an ATEX type certification is available up to category 1 GD (Zone 0 and 20).

Marking for explosive gas group IIC prevailing in H2 atmospheres is possible.



More information on resilient seated valves.

ACTUATORS & CONTROLS

Energy-efficient with uncompromising performance

EBRO actuators enable butterfly valves and knife gate valves to be actuated with high-efficiency. Due to precision alignment of the actuators with other components, applications benefit from increased energy-efficiency and reduced operating costs.

Customized configurations of individual product components are possible.



Z011-A / DVGW-Gas Wafer-type DN 20 – DN 1200



Z014-A / DVGW-Gas Lug-type DN 20 – DN 600



Z411-A / Z414-A Wafer/Lug-type Inner diameter for PE/PP DN 40 – DN 600



Z611-K / Z614-K Wafer/Lug-type Short Face-to-Face DN 50 – DN 300



EB-SYD (Scotch-Yoke) Pneumatic actuator Double-acting 27 Nm – 9.768 Nm



EB-SYS (Scotch-Yoke) Pneumatic actuator Single-acting 35 Nm – 3.590 Nm



More information on actuator technology.



More information on automation technology.



EP3 Electro-pneumatic positioner



SBU IO-Link Smart Box Unit Valve status monitoring



E50 – E210 Electric quarter-turn actuator 24V AC/DC, 230V AC, 400V AC Battery pack for emergency function 40 Nm – 4.000 Nm

H, HYDROGEN POWER CLEAR CHERISY OF THE FUTURE



HEADQUARTERS

EBRO ARMATUREN Gebr. Bröer GmbH

Karlstraße 8 D-58135 Hagen Germany

№ +49 2331 904-0
☑ post@ebro-armaturen.com
● www.ebro-armaturen.com

H2 HYDROGEN POWER

Stafsjö Valves AB

Störnings Väg 3 SE-618 95 Stavsjö Sweden

℃ +46 11 39 31 00
☑ sales@stafsjo.com
⊕ www.stafsjo.com

A Bröer Group company www.broeer-group.com

Follow us:



1,

H2 HYDROGEN PO

© EBRO ARMATUREN Gebr. Bröer GmbH All rights reserved. Subject to errors and omissions. 2025-04-02_EN



